



DECLARATION OF PERFORMANCE

- Unique identification code of the product type:
Door Stop International Composite Pedestrian Door Set (Glazed or Unglazed)
- Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
Products shall be allocated a unique identification number located on the base of the product and in the frames.
This number will also be recorded on all supporting documentation allowing for future identification.
- Intended use or uses of the construction product, in accordance with the application harmonized technical specification, as foreseen by the manufacture:
Pedestrian entrance to a domestic building
- Name, registered trade name or registered trade mark and contact address of the manufacture as required under Article 11(5):
Door Stop International LTD, Export drive, Huthwaite, Nottinghamshire, NG17 6AF, United Kingdom.
- Where applicable, name and contact address of the authorised representative whose mandate covers the task specified in Article 12(2):
- System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:
System 3
- In case of the declaration of Performance (DoP), concerning a construction product covered by a harmonized standard:
EN14351-1


Test Reports: BS6375-1 – Winkhaus; TR1177/C, Winkhaus; TR1192/C, Chiltern Dynamics; Chilt/P11012/Rev1. PAS23 – BSI; 261/7118070/1, Fullex certificate, FT753, Assa Abloy; TC144-8 issue 2, Assa Abloy TR082-10, Assa Abloy; 129, Chiltern Dynamics; Chilt/P11012/Rev1, Winkhaus; TR1177/B, Winkhaus; TR1192/B, ERA; 484, Exova 305691. PAS24 – BSI; 261/7118070/2, Fullex; certificate FT754, Assa Abloy; TR081-10, Assa Abloy; TR104-10, Chiltern Dynamics; Chilt/P11012/Rev1, Chilt/P12076/01, Chilt/P12076/02, Winkhaus; TR1177/A, Winkhaus TR1192A, ERA; 481, Exova; WIL322316A, BSI; 2370/7460036, Winkhaus TR1683, TR1640, Assa Abloy; 129. Annex B – BSI; 126/7118070, BBA; MT5877. BFRCDER Thermal Simulations – Chiltern Dynamics; Chilt/T11013-3/issue 1, BM TRADA; MTTFF14002 01, MTTFF14002 02, MTTFF14002 03, MTTFF14002 04.

8. Declared performance:

Characteristic	Test Standard	Declared value
Resistance to Wind Loads	EN12211	1200 Pa/ Class C2
Watertightness	EN1027	300 Pa/ Class 3A
Air Permeability	EN1026	300 Pa/ Class 2
Dangerous Substances	-	Non hazardous
Impact Resistance (glass or fragmental materials)	EN13049	Class One
Load bearing capacity of safety device	EN948	NPD
Ability to release (locked doors on escape routes only)	EN179	NPD
Thermal Performance	EN10077-1/ EN1077-2	1.0W/m ² K to 2.75W/m ² K
Operating Forces	EN12046-2	Less than 100N
Acoustics	EN ISO 140-3	NPD
Sizes(s)	Width – 808mm to 1030mm Height – 1978mm to 2129mm	

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacture identified in point 4.

I, the undersigned, hereby declare that the product(s) specified conforms to the directive(s) and standard(s) detailed above.

Signed: 

Print: ROBIN BARON