


Bi-Folding Doors

Visofold Slim 1000 Quickglaze











MULTI- POINT LOCKING

REAL ALUMINIUM BI-FOLDING DOORS FEATURE TWO HIGH SECURITY HOOKS AND A DEAD-BOLT TO ENSURE TOTAL PEACE OF MIND. UPGRADED LOCKING SYSTEMS ARE AVAILABLE, PLEASE SPEAK TO YOUR REAL RETAILER FOR DETAILS.

Range	Visofold Slim 1000 Quickglaze
Finish	Polyester powder coating to BS6496 (Marine Grade +60 microns)
Appearance	Square frame, sash and bead
Stock Colours	White gloss, RAL 7016m, RAL 9005m and Ral 7016m on white
System Glazing	Internally glazed Quickglaze system (no wedge gasketing on 28mm units)
Thermal Break	Polyamide thermally broken profile
Gaskets	Low line gasket for slimmer sightines
DER	Down to B rating using suitable double glazed unit

GET IN TOUCH

For more information or a fast quote, get in touch with the team or visit www.gfdhomes.co.uk



DATA SHEET

TEL: 01642 309 576

EMAIL: enquiries@gfdhomes.co.uk

TEL: 01642 309 576

Bi-Folding Doors

Visofold Slim 1000 Quickglaze

EMAIL: enquiries@gfdhomes.co.uk

U Value	Down to 1.6W/m2k with double glazing and 1.2 W/m2k with 44mm triple glazing
Locking System	2no hook bolts and a dead bolt by Smart
Security	PAS24 upgraded specification available
Cylinder	3 star UAP cylinder as standard
Hinges	Antislip pin on bottom roller hinges by Smart
Handles	Key locking handles by ERA
Max Number Of Sashes	6 sashes (Note: no external access on designs without lead door)
Frame Depth	70mm
Sash/Sash Sightline	122mm
Max o/a Height per sash	2500mm
Max o/a Width per sash	1200mm
Max Sash Weight	100kg
Minimum Sash Width	700mm
Glazing Sizes	28mm double glazing and 44mm triple glazing
Air Test	Class 4, 600Pa
Water Test	Class E, 750Pa
Wind Test	Class 4, 1800Pa
Add Ons	20mm and 42mm add on available
Cill Sizes	85mm, 150mm, 190mm and 225mm (integrated cill available open out only)
Threshold	Low level threshold options available (down to 15mm)
Service	
Quotes	Within 24 hrs
Orders	2-3 weeks
Delivery	On dedicated REAL vehicles (outer frame flat pack kit available)